

ENSTO

Enclosure PC

SPCP131304LG

| | |
|-------------|---|
| Code | SPCP131304LG |
| GTIN | 6438100101671 |
| Name | Enclosure PC Ensto Cubo S Size 125 x 125 x 35 mm, 25 mm base, plain sides, grey cover, PC |
| Description | Ensto Cubo S is a series of small to medium size enclosures available with knockouts or plain sides. The base of the enclosures is equipped with unique slots for printed circuit boards. |
| Vendor | Ensto Building Systems Finland Oy |



Technical specification

Certificates

Standards: EN 62208, GOST R

Colors

Color: Grey

Dimensions

| | |
|---------------------|-------------------------|
| Volume : | 546.875 cm ³ |
| Inner depth: | 20.5 mm |
| Length: | 35 mm |
| Outer base depth: | 25 mm |
| Width: | 125 mm |
| Height: | 125 mm |
| Outer cover height: | 10 mm |
| Size: | 125 x 125 x 40 mm |
| Weight: | 0.178 kg |

Material

| | |
|--------|-------------------------------------|
| Base: | Fiberglass reinforced polycarbonate |
| Cover: | Polycarbonate |

| | |
|---------------|---------------|
| Cover screws: | Polyamide |
| Gasket: | Polyurethane |
| Material: | Polycarbonate |

Mechanical

| | |
|------------------|-------|
| Impact strength: | IK 08 |
|------------------|-------|

Others

| | |
|-------------|--|
| Content: | Enclosure base, cover, cover screws, mounting screws |
| ETIM Class: | EC000261 |

Ratings

| | |
|-----------------------|---------------------------|
| Degree of protection: | IP66/IP67 |
| Flammability rating: | UL 746C 5 inch flame test |

Temperatures

| | |
|-------------------------------|----------------|
| Operating temperature: | -40 ... 80 °C |
| Short term temperature range: | -40 ... 120 °C |

Electrical values

| | |
|------------------------------|--------|
| Rated insulation voltage AC: | 1000 V |
| Rated insulation voltage DC: | 1500 V |

ETIM Technical specification

etim

| | |
|------------------------------|---------------|
| Height: | 125 mm |
| Depth: | 35 mm |
| Material: | Plastic |
| Material quality: | Other |
| Surface finishing: | Untreated |
| Colour: | Grey |
| RAL-number: | 7035 |
| With mounting plate: | No |
| Suitable for outdoor set-up: | Yes |
| With glazed door: | No |
| Impact strength: | IK08 |
| Degree of protection (IP): | IP67,EV006423 |

Packaging

Default package

| | |
|---------------|--------|
| Unit: | PCE |
| Package size: | 18 |
| Depth: | 383 mm |
| Width: | 258 mm |

| | |
|---------|-------------|
| Height: | 173 mm |
| Weight: | 3.446 kg |
| Volume: | 17.094822 l |