

STAR

IP65 BOXES FOR INDUSTRIAL SOCKETS

Description: IP65 SURFACE BOX 1x18 MOD. TRANSP.WINDOW

Reference:
CSN18PT

Characteristics:

Product type:	IP65 Boxes for industrial sockets
Exterior dimensions (Height x Width x Depth):	436x418x147 mm
Dimensions of the flush-fit gap (HxWxD):	-
Number of modules:	1x18 DIN rail
Installation:	Surface
Color:	Grey RAL 7035
Window:	Transparent tinted window
Weight (Kg):	2,51
Cable entry:	Top: 12xM20 - 6xM25 - 2xM32 - 1xM40 - Bottom: 10xM20 - 6xM25 - 2xM32 - 1xM40 - Oblong rear: 2xOB 25/32/25
Components:	-
Materials:	Halogen-free plastic materials. Frame and base: ABS. Transparent window: UV protection polycarbonate

Technical data:

Degree of protection:	IP65
Resistance to impact:	IK08
Glow wire resistance:	650 °C
Ball pressure test:	70 °C
Ambient temperature range:	-25 °C / +40 °C
Maximum operating voltage:	1000 V AC / 1500 V DC
Double insulation:	Class II

Certificates and standards:

Directive:	2014/35/EU
Standards:	UNE-EN 62208 and UNE-EN 61439-1 (as applicable)
Certificates:	



Codes:

EAN:	8431044180175
Customs tariff number:	85.38.10.00
ETIM 6.0:	EC000379

Description: IP65 SURFACE BOX 1x18 MOD. TRANSP.WINDOW