

LIGHT

IP54 JUNCTION BOXES

Description: IP54 WATERTIGHT JUNCTION BOX Ø84x50 WITH CONICAL CABLE GLANDS

Reference:

EP048

Characteristics:

Product type:	Watertight junction boxes with opaque cover and conical cable glands
Exterior dimensions (Height x Width x Depth):	Ø84x50 mm
Dimensions of the flush-fit gap (HxWxD):	-
Number of modules:	-
Installation:	Surface
Color:	Grey RAL 7035
Window:	Opaque cover
Weight (Kg):	0,07
Cable entry:	4xM25
Components:	-
Materials:	Halogen-free plastic materials. Base and cover: Shock-proof PS - Conical cable glands: PVC

Technical data:

Degree of protection:	IP54
Resistance to impact:	IK07
Glow wire resistance:	650 °C
Ball pressure test:	70 °C
Ambient temperature range:	-25 °C / +40 °C
Maximum operating voltage:	1000 V AC / 1500 V DC
Double insulation:	Class II

Certificates and standards:

Directive:	2014/35/EU
Standards:	IEC 60998-2-5
Certificates:	



Codes:


EAN:	8431044180007
Customs tariff number:	85.38.10.00
ETIM 6.0:	EC000113

LIGHT

IP54 JUNCTION BOXES

Description: IP54 WATERTIGHT JUNCTION BOX Ø84x50 WITH CONICAL CABLE GLANDS

Reference: EP048



Exterior dimensions (Height x Width x Depth):

Ø84x50 mm

Dimensions of the flush-fit gap (Height x Width x Depth):

-

Sustainability:

RoHS - REACH

Supply:

The boxes are supplied individually, shrink-wrapped and in multiple cardboard packaging, according to minimum packaging units. Boxes with conical cable glands are supplied with the cone assembled.

Packaging units: 134

Product end of life:

It does not require specific recycling operations.

Recommended applications:

Industrial and outdoor environments. Industrial sites, docks, swimming pools, garages, anywhere that requires a high degree of protection against dust, splashes and impacts.